

EMBEDDED COPLANAR STRIPS TRAVELING-WAVE PHOTOMIXERS

R.A. Wyss, T. Lee, J.C. Pearson,

Jet Propulsion Laboratory, California Institute of Technology, Pasadena, CA 91109

S. Matsuura[†], G.A. Blake,

*Division of Geological and Planetary Sciences, California Institute of Technology,
Pasadena, CA 91125*

C. Kadow[‡] and A.C. Gossard

Materials Department, University of California – Santa Barbara, Santa Barbara, CA 93106

Abstract

The electric field distribution in photomixers with electrodes deposited on the surface has already been calculated¹. It was shown that the strength of the electric field diminishes rapidly with depth. It was argued that the resulting reduction of the effective interaction volume of the device lowers the optical-to-heterodyne conversion. In this paper, we will present the results of our investigation on the influence of the electrode placement on the performance of photomixers.

We have fabricated and measured traveling-wave photomixer devices which have both embedded and surface electrodes – the nominal spacing between the electrodes was 2 μm . Devices were made using either low-temperature-grown (LTG)-GaAs or ErAs:GaAs as the photoconductive material. The dark current, photocurrent and RF emission were measured at nominally 1 THz. The experimental data show a surprising difference in the behavior of ErAs:GaAs devices when the electrodes are embedded. A factor of two increase in RF radiation is observed for electric fields < 20 kV/cm. No such improvement was observed for the LTG-GaAs devices. We argue that the distinctive behavior of the two photoconductive materials is due to differences in the crystal structure – LTG-GaAs is isotropic, while ErAs:GaAs is uniaxial. We find that the carrier mobility in-plane (parallel) to the ErAs layers in the ErAs:GaAs superlattice is larger than orthogonal to these layers. The data indicate that carrier velocity overshoot is responsible for the excess radiation produced for the embedded electrode ErAs:GaAs devices.

Present address: [†]Institute of Space and Astronautical Sciences, Kanagawa, Japan; [‡]Nortel Networks, Wilmington, MA 01887.

¹E.R. Brown, “A photoconductive model for superior GaAs THz photomixers,” *Appl. Phys. Lett.* **75**, 769 (1999).